tempo architectural

C3R LiteBar Kit

Tempo's C3R rigid linear lighting is the preferred method for illuminating small coves, undercabinets or simply highlighting a surface. The C3R LiteBar Kit effectively solves all the limitations of tapelight and adds significant value at a comparable price point.

. 4 1 (200) w. 1 (200) (200)



☐ C3RK-2-27 2.0W/ft | 2700K

60W Power Supply | 12V Power Feed Cable | 36 in

C3RK-2-35 2.0 W/ft | 3500K

60W Power Supply | 12V Power Feed Cable | 36 in

C3RK-3-27 3.3 W/ft | 2700K

100W Power Supply | 24V Power Feed Cable | 36 in

☐ C3RK-3-35 3.3 W/ft | 3500K

100W Power Supply | 24V Power Feed Cable | 36 in

Accessories

☐ SSD-120 Surge Suppression Device | 120V ☐ C3A-MTGBRKT-SURF Mounting Clips | Quantity 25 ☐ C3A-MTGBRKT-SURF-20 20° Mounting Clips | Quantity 25

For additional accessories, consult the specification sheet.

CONSISTENT COLOR

All C3R LEDs are selected and placed on printed circuit boards via Tempo's UniBin™ process which ensures consistent hue and color within the entire run. Color variations are held to within a maximum of a 2-step MacAdam ellipse.

SIMPLE MOUNTING


Because the LiteBars are designed with a built-in mounting track, they maintain straight and true for lay-in cove applications. If gravity isn't on your side, LiteBars may be secured with mounting clips or a bead of silicon adhesive. For combined curved and straight—run applications simply connect to the C3S LiteReel kit for express installation.


MICRO-MAINTAINABLE

Each 30ft C3R LiteBar Kit is comprised of 120 individual, 3 inch luminaires. Each mini luminaire is self-contained with its own LED board and thermally managed housing that can be serviced and maintained at a micro level. This modular CLiP® (Configurable Lighting Platform) is the foundation of Tempo's inventive product design.

QuickSpecs

- 2700K or 3500K CCT
- 80+ CRI
- 0° or 20° mounting clips
- 2.0 W/ft (200lm/ft) or 3.3W/ft (335lm/ft)
- $L_{85} > 86,000 hrs$
- Lightly frosted lenses
- CSA damp location listed













Specifications detailed are part of the 5-Day QuickShip kit program. For more options, such as additional color temperatures, high uniformity lenses or dimming, refer to the standard C3R product specifications.