# tempo architectural

## C3S LiteReel Kit

Tempo's C3S serpentine linear lighting is the preferred method for illuminating curvilinear coves and accenting intricate architecture. The C3S LiteReel Kit effectively solves all the limitations of tapelight and adds significant value at a comparable price point.

#### LiteReel Kit Continuous 30 feet of C3S

☐ C3SK-2-27 2.0W/ft | 2700K

60W Power Supply | 12V

Power Feed Cable 36 in

2.0 W/ft | 3500K ☐ C3SK-2-35

60W Power Supply | 12V

Power Feed Cable 36 in

☐ C3SK-3-27 3.3 W/ft | 2700K

100W Power Supply | 24V

Power Feed Cable | 36 in

☐ C3SK-3-35 3.3 W/ft | 3500K

> 100W Power Supply | 24V Power Feed Cable | 36 in

☐ C3SK-3-30-DIM 90W 0-10V Dimmable Power Supply | 24V Power Feed Cable

> Mounting and installation accessories included

#### Accessories

☐ SSD-120 Surge Suppression | 120V ☐ C3A-TK-FX Mounting Track | 30ft

For additional accessories, consult the specification sheet.

#### **MULTI-AXIS FLEXIBILITY**

Zigzags or loop-the-loops, no architecture is off limits for the C3S. To ensure even illumination, the flexible mounting track is recommended. For combined curved and straight-run applications simply connect to the C3R LiteBar kit for express installation.

#### MICRO-MAINTAINABLE

Each 30ft C3S LiteReel Kit is comprised of 113 individual, 3 inch luminaires. Each mini luminaire is self-contained with its own LED board and thermally managed housing that can be serviced and maintained at a micro level. This modular CLiP® (Configurable Lighting Platform) is the foundation of Tempo's inventive product design.

#### **CONSISTENT COLOR**

All C3S LEDs are selected and placed on printed circuit boards via Tempo's UniBin™ process which ensures consistent hue and color within the entire run. Color variations are held to within a maximum of a 2-step MacAdam ellipse.

### **QuickSpecs**

• 2700K or 3500K CCT


•  $L_{85} > 86,000 hrs$ 


• 80+ CRI

Lightly frosted lenses

• 2.0 W/ft (200lm/ft) or 3.3W/ft (335lm/ft)

 CSA damp location listed











Specifications detailed are part of the 5-Day QuickShip kit program. For more options, such as additional color temperatures, high uniformity lenses or dimming, refer to the standard C3S product specifications.